


SERIOLA D TH



Heat transfer fluid

Cleaning additive for heat transfer circuits.

APPLICATIONS

Heat transfer oils circuits
cleaning before drain

- **SERIOLA D TH** is used diluted in the fluid for circuits requiring cleaning.
- **SERIOLA D TH** is only used for cleaning operations
- Add 5 % minimum of **SERIOLA D TH** in the circuit 24 to 48 hours before oil change while maintaining the fluid circulation at the normal use temperature (approximately 270 °C).
- Replace the filters before refilling the circuit with new oil.

ADVANTAGES

high heat transfer
efficiency

Running safety

- **SERIOLA D TH** has a high detergency and dispersiveness level ensuring an efficient cleaning of the heat transfer circuit. Excellent thermal stability.
- **SERIOLA D TH** is completely miscible with all mineral-based heat transfer oils. Please contact technical support for details of use with synthetic heat transfer oils.

CARACTERISTIQUES TYPES	METHODS	UNITS	SERIOLA D TH
Specific gravity at 15 °C	ISO 3675	kg/m ³	910
Kinematic viscosity at 40 °C	ISO 3104	mm ² /s	24.5
Kinematic viscosity at 100 °C	ISO 3104	mm ² /s	4.8
Flash point OC	ISO 2592	°C	203
Aniline point	ISO 2977	°C	58

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités
21-06-2010 (supersedes 28-11-2001)
SERIOLA D TH
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from www.quick-fds.com.